BMW Group Mobile Tradition



BMW R 24

		1010
Engine	Begin of the Production	1948
	End of the Production	1950
	Internal Designation	224/1
	Motor Type	four-stroke single-cylinder vertical
	Bore	68 mm
	Stroke	68 mm
	Displacement	247 ccm
	Max Power	12 hp
	Rpm (Max Power)	5600 rpm
	Compression Ratio	6.75:1
	Valves	ohv
	Carburetion System	1 x Bing type AJ 1/22/140 b
	Engine Lubricating System	forced-feed lubrication
	Oil Pump	gear pump
Power transmission	Clutch	single-plate, dry
	Number of Gears	4
	Shifting	foot switching (+ auxiliary manual switch on gearing block)
	Gearbox Ratios	6.1/3.0/2.04/1.54
	Rear Wheel Ratio	4.18:1 or 4.25:1
	Bevel/Crownwheel	11/46 or 8/34 teeth
Electrical system	Generator	6 V/45 W
	Ignition System	battery ignition
	Spark Plugs	Bosch W 240 T1 or Bosch W 225 T1
Chassis	Designation	224/1
	Frame	closed steel twin-loop frame, bolted
	Front Wheel Suspension	telescopic fork
	Rear Wheel Suspension	rigid
	Wheel Rims	2.5 x 19 deep-bed
	Tyres front	3 x 19
	Tyres rear	3 x 19
	Brakes front	drum brake Ø 160 mm
	Brakes rear	drum brake Ø 160 mm
Dimensions and weights	Length	2020 mm
	Width	750 mm
	Height	710 mm (Saddle)
	Fuel Tank Capacity	121
	Unladen Weight, Full Tank	130 kg
	PermittedWeight Limit	290 kg
	Fuel Consumption	approx. 3,5 l/100 km
	Oil Consumption	approx. 1 l/1000 km
	Top Speed	95 kph
	Numbers Produced	12.020
	Price	1.750,- DM