

BMW R 60/6

BMW Group
Mobile Tradition



The Ultimate
Riding Machine

Engine	Begin of Production	1973
	End of Production	1976
	Motor Type	four-stroke, two-cylinder, horizontally-opposed Boxer engine, air-cooled
	Bore	73,5 mm
	Stroke	70,6 mm
	Cubic Capacity	599 ccm
	Max Power	40 hp (29,5 KW)
	Rpm (Max Power)	6400 rpm
	Max Torque	49 Nm
	Rpm (Max Torque)	5000 rpm
	Compression Ratio	9.2:1
	Valves per Cylinder	2
	Valve Control	ohv, using push rod and rocker arm
	Carburation System	2 slide carburetors, Bing 1/26/111-112 or 1/26/123-124
Power transmission	Engine Lubrication	wet sump
	Clutch	dry single plate, with diaphragm spring
	Number of Gears	5
	Gear Selection	dog-type gearbox (ratchet foot lever)
	Gear Ratios	4.4/2.86/2.07/1.67/1.50:1
	Rear Wheel Ratio	1:3.36
	Bevel/Crownwheel	11/37 teeth
Electrical system	Ignition	battery ignition
	Alternator	Bosch 12 V/280 W
	Starter	Bosch 0.5 hp
	Spark Plugs	Bosch W 230 T 30/Beru 230/14/3 A/
Chassis	Type of Frame	double-loop tubular frame with bolt-on rear section
	Front Suspension	telescopic fork with hydraulic shock absorber
	Rear Suspension	long swinging arm with adjustable strut
	Spring Travel front/rear	208 / 125 mm
	Rims front	1.85 B 19
	Rims rear	2.15 B 18
	Tyres front	3.25 S 19
	Tyres rear	4.00 S 18
	Brakes front	duplex drum brake 200 mm dia
	Brakes rear	simplex drum brake 200 mm dia
Dimensions and weights	Length	2180 mm
	Width	740 mm
	Height	1080 mm
	Wheel Base	1465 mm
	Ground Clearance	165 mm
	Tank Capacity	18 l (optional 22 tank at extra charge)
	Unladen Weight, full Tank	210 kg
	Max permissible Weight	398 kg
	Fuel Consumption	5,5 l/100 km (at constant 90 kph)
	Acceleration 0-100 kph	7,7 sec
	Top Speed	167 kph
	Number Sold	13.511
	Price	5.992,- DM