

BMW R 65

BMW Group
Mobile Tradition



The Ultimate
Riding Machine

Engine	Begin of Production	1978
	End of Production	1985
	Motor Type	four-stroke, two-cylinder, horizontally-opposed Boxer engine, air-cooled
	Bore	82 mm
	Stroke	61,5 mm
	Cubic Capacity	649,6 ccm
	Max Power	45 hp (33 KW) [50 hp (37 KW)]
	Rpm (Max Power)	7250 rpm [7250 rpm]
	Max Torque	50 Nm [52,3 Nm]
	Rpm (Max Torque)	5500 rpm [6500 rpm]
	Compression Ratio	9.2:1
	Valves per Cylinder	2
	Valve Control	ohv, using push rod and rocker arm
Power transmission	Carburation System	2 constant depression carburettors, Bing 64/32/2030-2040 or 64/32/307-308
	Engine Lubrication	wet sump
	Clutch	dry single plate, with diaphragm spring
	Number of Gears	5
	Gear Selection	dog-type gearbox (ratchet foot lever)
	Gear Ratios	4.4/2.86/2.07/1.67/1.50:1
	Rear Wheel Ratio	1:3.44
Electrical system	Bevel/Crownwheel	9/31 teeth
	Ignition	Contact-free electronic ignition
	Alternator	Bosch 280 W
	Starter	Bosch 0.7 kW
Chassis	Spark Plugs	Bosch W 5 D/Beru 14-5D/Champion N 6 Y
	Type of Frame	double-loop tubular frame with bolt-on rear section
	Front Suspension	telescopic fork with hydraulic shock absorber
	Rear Suspension	long swinging arm with adjustable strut
	Spring Travel front/rear	175 / 110 mm
	Rims front	1.85 B 19
	Rims rear	2.50 B 19
	Tyres front	3.25 S 19
	Tyres rear	4.00 S 19
	Brakes front	single disc brake 260 mm dia
Dimensions and weights	Brakes rear	simplex drum brake 200 mm dia
	Length	2110 mm
	Width	688 mm
	Height	1090 mm
	Wheel Base	1400 mm
	Ground Clearance	130 mm
	Tank Capacity	22 l
	Unladen Weight, full Tank	205 kg
	Max permissible Weight	398 kg
	Fuel Consumption	4,6 l/100 km (at constant 90 kph)
	Acceleration 0-100 kph	5,9 sec [5,8 sec]
	Top Speed	175 kph
	Number Sold	29.454
	Price	6.980,- DM